



Danelaw[®]

LOW RESISTANCE BREATHABLE TILE AND SLATE ROOF UNDERLAYS

PRODUCT BROCHURE

+44 (0)1327 701910
sales@hambleside-danelaw.co.uk
www.hambleside-danelaw.co.uk

INTRODUCTION

Hambleside Danelaw is an established UK manufacturer of roofing accessories and ventilation products. It has over forty years of experience and expertise supplying engineered solutions to the construction industry.

The product range provides an effective solution to protect the building and its occupants from the harmful effects of interstitial condensation and external climatic conditions including wind, snow and wind driven rain.

Danelaw® LR roof tile and slate underlays are three-layer composite flexible membranes. The top and bottom layers are non-woven spun bond polypropylene encapsulating a microporous film core. The three layers are laminated together using the latest thermal bonding and ultrasonic technologies to prevent delamination.

The products have been developed for use in cold and warm pitched roof applications, and are suitable for use draped and unsupported, or fully supported on sarking or insulation boards. The products should be installed in accordance with the recommended installation guidelines and will provide the following key functions:


- Temporary weather protection prior to tile or slate fixing during construction
- Reduced wind loading on the outer roof covering
- Reduced condensation risk in the roof spaces
- Improved weathertightness of the completed roof construction
- Improved durability of the roof construction
- Improved airtightness for improved energy efficiency

THE CONTROL OF CONDENSATION IN PITCHED ROOFS

The company recognise that good design and specification of reputable building products is essential to enable architects to comply with the relevant Building Regulations and British Standards. Building Regulations Approved Document C requires that all roofs are designed and constructed to ensure their structure and thermal performance are not adversely effected by interstitial condensation.

This requirement can be met if the pitched roof is designed and constructed in accordance with Annex H of BS 5250 '*Code of practice for the control of condensation in buildings*'. In addition, BS 5534 '*Slating & tiling for pitched roofs and vertical cladding - code of practice*' recommends the provision of ventilation in accordance with the requirements of BS 5250.

The level of ventilation required and location of the ventilation openings will depend on the type of roof covering, building type and use, the design, size, roof pitch, roof tile underlay type and the amount of water vapour entering the roof void from habitable rooms below.



The simple combination of Danelaw LR breathable roof tile underlay and the Danelaw eaves ventilation products or the CON6+ dry fix ventilated ridge system provides an effective and simple solution to comply with British Standards, Building Regulations and NHBC Technical Standards, Chapter 7.2 Pitched roofs.

AIRTIGHT ROOF COVERINGS

The use of a Low Resistance underlay reduces the risk of condensation in the loft or roof space, but does increase the risk of condensation in the batten space leading to premature decay of the battens unless there is sufficient air movement through the roof covering. Where the outer roof covering is not classified as sufficiently 'air permeable' in accordance with BS 5534 Annex L, then BS 5250 recommends that additional ventilation may be required between the underlay and outer roof covering.

FULLY SUPPORTED UNDERLAYS

Where Low Resistance roof tile underlays are used in applications where the underlay is fully supported by materials that offer a higher resistance to the passage of vapour, such as plywood or OSB, then the underlay should be treated, for design purposes, as a High Resistance (HR) underlay.

UNVENTILATED ROOF CONSTRUCTION

The construction and requirements for pitched roofs to be constructed without any ventilation is not covered by BS 5250 or any other Standard. The requirements to both construct this type of roof in respect of the level of vapour sealing required, and for the level of sealing to be maintained for the life of the roof is extremely onerous and difficult to achieve in practice and is therefore not recommended where the guidance in BS 5250 can be followed.

WIND LOADING

Danelaw® LR roof tile and slate underlays have been independently tested by the Building Research Establishment and British Board of Agrément. The physical properties of the products are adequate to resist the wind loads imposed on the underlay and will therefore adequately reduce the wind uplift forces acting on the outer roof covering.

The products are satisfactory for use in unsupported pitched roof systems for the BRE defined geographical wind zones given in the table below. The Danelaw® LR120TT and LR150TT are supplied with an integral tape to tape system and is as an alternative option to a batten for restraining the horizontal overlap, or separate lap tape use.

All Danelaw LR underlays are suitable for wind zones 1 to 5 at 345mm batten gauge when used with separate lap tape.

PRODUCTS	250mm BATTEN GAUGE WITH LAP RESTRAINING BATTEN	345mm BATTEN GAUGE WITH LAP RESTRAINING BATTEN	345mm BATTEN GAUGE WITH INTEGRAL TAPED HORIZONTAL OVERLAP
Danelaw® LR 120	Zones 1 to 5	Zones 1 to 3	-
Danelaw® LR 120TT	-	-	Zones 1 to 5
Danelaw® LR 135	Zones 1 to 5	Zones 1 to 2	-
Danelaw® LR 150	Zones 1 to 5	Zones 1 to 3	-
Danelaw® LR 150TT	-	-	Zones 1 to 5
Danelaw® LR 180	Zones 1 to 5	Zones 1 to 4	-


NOTE 1: Zone suitability applies only for underlays in applications where a well-sealed ceiling is present, ridge height is not greater than 15m, roof pitch is between 12.5° and 75°, site altitude is not greater than 100m, and no significant site topography is present. Other applications might require underlays with greater wind uplift resistance and it is advisable to seek professional advice from our Technical Department.

NOTE 2: Zones 3 and 4 apply to Northern Ireland. Zone 3 applies to the Scilly Isles and Channel Islands. Zone 5 applies to the Shetland Islands.

Please see UK geographical wind map and zonal boundaries on separate product specification sheets and labelling.



RELATED HAMBLESIDE DANELAW PRODUCTS AND ROOFING ACCESSORIES




Rigid Underlay Support Tray
Product Code: HDRFST



Roofing Underlay Support Tray
Product Code: HD 3000



FOR HIGH LEVEL VENTILATION
Dry Fix Rollout Ridge and Hip
Product Code: HD ROR6 & HD CON6+



FOR LOW LEVEL VENTILATION
Eaves and Soffits Vents
HD 12000U and HD 8000

TECHNICAL SUPPORT

For further details about how we can support your technical needs, please email:

techhelp@hambleside-danelaw.co.uk

RIBA APPROVED CPD PRESENTATIONS

For details about our RIBA approved CPD presentation, please email:

Paul Turner, Business Development Manager
paul.turner@hambleside-danelaw.co.uk

AREA SALES MANAGERS IN YOUR LOCATION:

EAST MIDLANDS

Kris Brentnall

kris.brentnall@hambleside-danelaw.co.uk
07710 573013

SOUTH EAST

Russell Evans

russell.evans@hambleside-danelaw.co.uk
07801 933967

SOUTH WEST AND SOUTH WALES

Richard Spreag

richard.spreag@hambleside-danelaw.co.uk
07710 573005

WEST MIDLANDS & WALES

Mark Holliday

mark.holliday@hambleside-danelaw.co.uk
07710 573002

NORTH

Terry Muse

terry.muse@hambleside-danelaw.co.uk
7710 573006

SCOTLAND

Mike Lemmon

mike.lemmon@hambleside-danelaw.co.uk
07710 573023

BUSINESS DEVELOPMENT MANAGER

Alan Collier

alan.collier@hambleside-danelaw.co.uk
07710 573003

UK-WIDE : FIELD TECHNICAL SUPPORT

Paul Lambert

paul.lambert@hambleside-danelaw.co.uk
07712 526257

Hambleside Danelaw Limited

Hambleside Danelaw Building Products Ltd has a continuing product development programme. With any updates or changes to our products, we try to ensure communication is regular to our customers and stakeholders. In accordance with our policy for continuous improvement we reserve the right, should the need arise, to amend product specifications without prior notice. In turn, products may slightly differ at the time of the print of this publication. Terms and Conditions of Sale are available upon request.

All images are for illustration purposes only and Hambleside Danelaw Ltd reserve the right to amend specifications without prior notice. All content as recommended by Hambleside Danelaw Ltd. Intellectual property of Hambleside Danelaw Ltd, permission required to reproduce all content of this publication.