



CONTI-SOAKERS

30 YEAR GUARANTEE

The continuous GRP soakers provide a quick and efficient method of forming a secret gutter or weatherproof solution at the tile or slate roof side abutment junction.



FEATURES AND BENEFITS

- Quick and simple to install
- Thermally stable
- UV and acid rain resistant
- Lead alternative
- Reduced theft risk
- Creates no harmful run off into water courses
- Mortar bonding strip for tile roof application

APPLICATION

The range of GRP Conti-Soakers for tile and slate roofs are available in lipped and unlipped options. The lipped version is fixed directly into the wall, alternatively the unlipped version can be installed with a stepped or GRP cover flashing.

The Conti-Soaker for Scottish slate roofs is supplied unlipped and installed in the same way or terminated behind a render stop or bellcast drip.

The Conti-Soaker for use with tile verge clips is reduced in width to allow the use of a wide range of verge clip designs.

MATERIAL AND COLOUR


GRP and Anthracite

CERTIFICATION


BBA Certificate 87/1915



PRODUCT, CODE AND DIMENSIONS




For tile roofs, code: HD CST-L
Dimensions: H150 x W170 x L3000mm




For tile roofs, code: HD CST
Dimensions: H140 x W170 x L3000mm


♻️ Contains recycled glass



For slate roofs, code: HD CSS-L
Dimensions: H150 x W170 x L3000mm



For slate roofs, code: HD CSS
Dimensions: H140 x W170 x L3000mm



For Scottish slate roofs, code: HD SCSS
Dimensions: H200 x W160 x L3000mm




For tile roofs using verge clips, code: HD CSTC
Dimensions: H140 x W120 x L3000mm

RELATED PRODUCTS



Individual Dry Soakers

Create a weatherproof joint at abutments. Compatible with a wide range of flat tiles and slates, codes: HD MDS, RRS, RTS, SRRS, DTS, RCS, PCS, SS500 and SS600



Fast Flash

An environmentally friendly, lead-alternative flashing. Available in 3 colours of 5 metre rolls in 4 widths, codes: Fast Flash 140, 280, 370, 560



Tile & Slate Breathable Roofing Underlays

Available in four weights, two with optional integral lap tapes and widths of 1.0m or 1.5m, codes: DLR120, DLR120TT, DLR135, DLR150, DLR150TT and DLR180